

The World's Most Trusted Industrial Bolting Systems

Digital jGun™

LCD 화면과 함께 FRL이 필요없는 최초의 토크 건



특성

- 별도의 필터/공압조절기/윤활장치(FRL)가 필요 없는 단 하나뿐인 공압 토크렌치
- 화면을 통해 입력된 토크 값을 즉시 확인
- 손쉬운 토크 조절을 위한 일체형 공압조절기
- 새로운 설계된 모터로 윤활과 드라이어가 필요 없음
- 좀 더 편리한 작동과 유지보수를 위한 회전 계측장치 내장
- 작동 소음과 진동을 감소시키는 소음기 내장
- 동급 토크렌치 중 가장 높은 무게 대비 출력
- HYTORC Washer 또는 HYTORC Nut 와 함께 사용할 수 있음



24 Hour Service

TORQUE GUN
— A HYTORC COMPANY —

Accessories



HYTORC WASHER

Replace your standard washer with the revolutionary HYTORC Washer to optimize your bolted joint. This simple upgrade is the best value in the industry for increased safety, speed and accuracy on bolting jobs.



HYTORC NUT

The HYTORC Nut™ is a perfect solution for limited radius applications. Applications set into a pocket or a counter bore pose a problem with conventional tooling. Standard drive extensions and machined down accessories compromise the safety of the operator.



OFFSET LINKS

For tight spaces and limited overhead clearance, the offset link is the answer. This slim-design link works with our full line of pneumatic and hydraulic tools and is available with various sized hex cartridges to fit on all applications.

Dimensional Data



Model	Torque Range	Drive	Bolt Sizes	H	L	R	RPM	Weight w/o Arm	Weight w/ Arm
	Ft. Lbs./Nm			Inches/mm				Lbs./Kg	
DJ-.25	N/A	3/4"	N/A	7.55/191.77	6.95/176.53	2.5/63.5	N/A	N/A	N/A
DJ-.5	N/A	3/4"	N/A	7.55/191.77	8.03/203.96	2.58/65.53	N/A	N/A	N/A
DJ-1	N/A	3/4"	N/A	7.55/191.77	8.79/223.26	2.58/65.53	N/A	N/A	N/A
DJ-2	540-2090/735-2830	1"	1" to 1 5/8"	8.09/205.5	10.79/274.06	3.25/82.55	5.5	16.5/7.4	19.7/8.9
DJ-3	856-3180/1161-4312	1"	1" to 1 7/8"	8.09/205.5	11.46/291.08	3.25/82.55	4.5	17.7/8.0	21/9.5
DJ-5	N/A	1.5"	N/A	8.09/205.5	12.26/311.4	4.15/105.41	N/A	N/A	N/A
DJ-8	N/A	1.5"	N/A	8.09/205.5	13.49/342.64	4.56/115.82	N/A	N/A	N/A